

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** MAXIMUM TEMPERATURE THREAD SEALANT WITH PTFE 50 ML  
**Item No:** 56750  
**Product Type:** Anaerobic

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
BISPHENOL A FUMARATE RESIN 39382-25-7	20-40	Not listed	Not Listed
POLYGLYCOL DIMETHACRYLATE 25852-47-5	20-40	Not listed	Not Listed
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<5	5 mg/m <sup>3</sup> , TWA	6 mg/m <sup>3</sup> TWA
POLYTETRAFLUOROETHYLENE 9002-84-0	<5	Not listed	Not Listed
SACCHARIN 81-07-2	<5	10 mg/m <sup>3</sup>	Not Listed
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	0.1-1.0	Not listed	Not Listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause moderate eye irritation. May cause moderate skin irritation. Note: This product does not contain microcrystalline silica.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Repeated skin contact may cause allergic skin reactions.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<5			Amorphous Silica, Group 3: Vol. 68: 1997
POLYTETRAFLUOROETHYLENE 9002-84-0	<5			Group 3 Supplement 7, 1987; Monograph 19, 1979
SACCHARIN 81-07-2	<5	Delisted April 2000		Group 3: Vol 73, 1999

**Medical Conditions Recognized as Being Aggravated by Exposure:** Allergy, eczema, skin conditions.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.  
**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** >200°F  
**Recommended Extinguishing Media:** Carbon dioxide, Dry chemical, Alcohol foam  
**Special Fire-Fighting Procedures:** Firefighters should wear self-contained breathing apparatus.  
**Hazardous Products of Combustion:** Oxides of carbon, Oxides of nitrogen  
**Unusual Fire/Explosion Hazards:** None

**Lower Explosive Limit:** Not determined

## **5. FIRE FIGHTING MEASURES**

**Upper Explosive Limit:** Not determined

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

## **7. HANDLING AND STORAGE**

**Storage:** Store below 100 degrees F.  
**Handling:** Avoid prolonged skin contact. Keep away from eyes.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses..  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.  
**Respiratory Protection:** Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** White paste  
**Odor:** MILD  
**Boiling Point:** >300°F  
**pH:** Does not apply  
**Solubility in Water:** Insoluble  
**Specific Gravity:** 1.02  
**VOC Content(Wt.%):** 0.78%  
**Vapor Pressure:** <5 mmHg @ 80°F  
**Vapor Density (Air=1):** Heavier than air  
**Evaporation Rate:** Not Determined

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Stable at normal conditions  
**Hazardous Polymerization:** WILL NOT OCCUR.  
**Incompatibilities:** Metal salts, heat and amines.  
**Conditions to Avoid:** Heat  
**Hazardous Products of Combustion:** Oxides of carbon, Oxides of nitrogen

## **11. TOXICOLOGICAL INFORMATION**

See Section 3

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

**DOT Shipping Name:** Unrestricted  
**Hazard Class:** None  
**UN/ID Number:** None

### **IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/ID Number:** None

**Product Name:** MAXIMUM TEMPERATURE THREAD  
SEALANT WITH PTFE 50 ML

**Item No:** 56750

**IMDG**

**Proper Shipping:** Unrestricted  
**Hazard Class:** None  
**UN Number:** None  
  
**Marine Pollutant:** None

**15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

**TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 1.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** February/29/2008

**Revision** 5

**Number:**

**Telephone No.:** 1-87-Permatex (877) 376-2839